



INVERNIZZI

Plywood Tradition



CONTREPLAQUÉ PEUPLIER “TUTTO Pioppo”

Le contreplaqué peuplier INVERNIZZI est un produit naturel fabriqué à partir de placages en peuplier [au moins 3 couches] superposés avec les fils croisés et collés.

Il est fabriqué en conformité avec les normes de contrôle des émissions de formaldéhyde et peut également être offert avec plusieurs certifications : FSC ou PEFC, E1 ou CARB Phase 2, CE ou CE+.

Les caractéristiques principales des panneaux sont : couleur claire, légèreté, faces et intérieurs uniformes et bonnes performances mécaniques.

Tout ça est réalisé dans le respect de l'environnement avec la moindre utilisation d'additifs chimiques.

INVERNIZZI's poplar plywood is a natural product manufactured using poplar veneers [at least 3 plies], which have been overlaid with the wood grains running perpendicularly and glued.

It is manufactured according to the formaldehyde emission control rules and can be proposed also provided of FSC or PEFC, E1 or CARB Phase 2, CE or CE+ certificates.

The main features of the panels are: light color, low weight, uniform faces and cores and good technical performances.

The product is manufactured in the maximum respect for the environment with the most limited use of chemical additives.

CONTREPLAQUÉ PEUPLIER “TUTTO Pioppo”



INVERNIZZI
Plywood Tradition

	ÉCOLOGIQUE ET DURABLE		100% PEUPLIER DURABLE		FACILE À TRAVAILLER
	GREEN AND SUSTAINABLE		100% POPLAR SUSTAINABLE		EASILY WORKABLE
	SAIN POUR TA MAISON		LÉGER ET RÉSISTANT		CONFORME AVEC F-4 ÉTOILES
	HEALTHY FOR YOUR HOME		LIGHT AND RESISTANT		COMPLIANT WITH F-4 STARS
 LE CONTREPLAQUÉ PEUPLIER «Tutto Pioppo» LW INVERNIZZI répond aux crédits LEED et aux standards WELL (voir fiche dédiée) <i>INVERNIZZI "TUTTOPioppo" LW POPLAR PLYWOOD satisfies LEED credits and WELL standards (see dedicated leaflet)</i> 					

SPÉCIFICATIONS TECHNIQUES TECHNICAL FEATURES

QUALITÉ DES FACES FACE GRADES	FRONTE FACE	• I [AB] • II [B]	• III [BB] • IV [C]
	RETRO BACK	• III [BB] • IV [C]	
COLLAGES GLUES	CLASSE 1 CLASS 1	• UF[IF20]E1 • EPA-TSCA/CARB Ph.2	
	CLASSE 2 CLASS 2	• MUF [A100] • MUF - AW100	
ÉPAISSEURS THICKNESS	MINIMO MINIMUM	• 3 mm	Peut varier en fonction du format demandé. May vary depending on the chosen size.
	MASSIMO MAXIMUM	• 50 mm	
FORMATS STANDARD STANDAR SIZES	• 2520 x 1870 • 2500 x 1220 • 2440 x 1220 • 2520 x 1530	FORMATS “GRANDS” “BIG” SIZES	• 3130 x 2120 • 3130 x 1850 • 3100 x 1530 • 2120 x 3130
Formats spéciales disponibles sur demande. Toutes les productions sont soumises à l'acceptation de la maison, les éventuelles surcharges et les quantités minimales sont à convenir au moment de la commande. Panneaux également disponibles avec des caractéristiques de réaction au feu "Ignipascamp" [voir fiche dédiée]. Special sizes available on request. All productions are subject to the mill's acceptance, surcharges and minimum quantities to be agreed at the time of each order. Panels available also with fire reaction features "Ignipascamp" [see dedicated leaflet].			

CERTIFICATIONS CERTIFICATIONS



APPLICATIONS APPLICATIONS



MEUBLES / DÉCORATION D'INTÉRIEURS
FURNITURE / INTERIOR DESIGN



VÉHICULES DE LOISIR
RV/CAMPER/CARAVAN



BATEAUX
MARINE YACHTS



CONSTRUCTION
BUILDING